



2 Special Clevis Sub-Assembly GTKR/SUN

Product information

General: For 2-leg slings.

Temperature range: -40 up to 200 °C

Safety factor: 4:1

Grade: 12

| Part Code | Code | Chain diameter | WLL ton | EWL | can be used with single hook acc. DIN15401 up to nr. | WLL 45- 60° ton | d mm | t mm | w mm | e mm | Weight kg | Delivery time |
|--------------|---------------|----------------|---------|-----|--|-----------------|------|------|------|------|-----------|---------------|
| 403100340060 | GTKR/SUN 2-7 | 7 | 3.35 | 203 | 6 | 2.36 | 19 | 160 | 95 | 203 | 1.5 | 30 |
| 403100430060 | GTKR/SUN 2-8 | 8 | 4.25 | 203 | 6 | 3 | 19 | 160 | 95 | 203 | 1.52 | 30 |
| 403100710060 | GTKR/SUN 2-10 | 10 | 7.1 | 221 | 10 | 5 | 23 | 170 | 105 | 221 | 2.67 | 30 |
| 403101120060 | GTKR/SUN 2-13 | 13 | 11.2 | 257 | 10 | 8 | 30 | 190 | 110 | 257 | 5 | 30 |
| 403101700060 | GTKR/SUN 2-16 | 16 | 17 | 353 | 12 | 12.2 | 38 | 275 | 150 | 353 | 10.37 | 30 |

Blueprint

