


Lifting-belt-sling.



Product information

Lifting belt slings for heavy loads up to 100 tons.

For heavy loads up to 100 tons

With the lifting belt slings from LIFT-TEX[®] you can lift loads of up to 100 tons. This truly outstanding development is based on a manufacturing technology with a construction allowing a larger lifting area of the belt with shortened soft eyes. Guaranteed double service life.

Guaranteed double service life

The core is protected by a highly abrasion and cut resistant protection sleeve. This double the service life of normal lifting slings.

Lifting belt slings

The new LIFT-TEX lifting belt slings are available in width up to 300 mm.

Slings are made with two soft, reinforced eyes on each end for easy crane hook handling. Special abrasion resistant cut protection sleeves are additionally available in the required length.

Standard type:

Protection sleeves: in addition to the standard types, or separately as replacement in required length (full length) available.

Working length: From 2 m up to 50 m.

Always apply and use extra protections to protect the sling from sharp edges, abrasion, wear and tear, due to the shape of the boat (keel & side).

Contact CERTEX for further information.

Material: 100% High Tenacity Polyester (core and cover).

Marking: According to standard, Label in a reinforced plastic seal.

Standard: EN 1492-1

Safety factor: 7:1

Part Code	WLL ton
342100100000020	1
342100200000020	2
342100300000020	3
342100400000020	4
342100500000020	5
342100600000020	6
342100800000020	8
342101000000020	10
342101500000020	15
342102000000020	20
342102500000020	25
342103000000020	30
342104000000020	40
342105000000020	50