



Stainless steel sling 2-leg RCM-RCL-RCB

Product information

REMA[®]

SS

Rema®'s Grade 6 Stainless Steel Chain Slings are meticulously crafted using top-tier stainless steel (AISI 316), our slings are not just durable but also versatile. With the availability of individual components, we ensure a sustainable and customizable solution tailored to your specific lifting requirements. Our stainless steel assemblies are trusted across a myriad of industries such as construction, food & beverage, healthcare, aerospace, marine, and beyond.

Utilization Features:

1. **Durability:** Made with premium AISI 316 stainless steel, ensuring longevity and resistance to corrosion.
2. **Versatility:** Suitable for a range of lifting operations with various assembly options.
3. **Safety:** Comes with a CE-mark and a safety factor of 4, ensuring utmost safety during operations.
4. **Adaptability:** Individual component availability for a tailored lifting solution.

Markets/Applications:

- **Construction:** Ideal for heavy-duty lifting and construction site operations.
- **Food & Beverage:** Stainless steel ensures hygiene and cleanliness, making it perfect for food-related lifting tasks.
- **Medical:** Suitable for lifting medical equipment and supplies.
- **Aerospace:** Can be used for lifting aerospace components.
- **Marine:** Resistant to corrosion, making it perfect for marine applications.

Link to components

- 2 x RC stainless steel chain | masterlink RCM | 2 x connecting link RCL | 2 x clevis sling hook RCB | AISI 316 TAG

Marking: CE-marked

Safety factor: 4

Grade: 6

Part Code	WLL ton
R2689206-1	1.26
R2689206-1,5	1.26
R2689206-2	1.26
R2689207-1	1.75
R2689207-1,5	1.75
R2689207-2	1.75
R2689208-1	2.24
R2689208-1,5	2.24
R2689208-2	2.24
R2689210-1	3.5
R2689210-1,5	3.5
R2689210-2	3.5
R2689213-1	5.95
R2689213-1,5	5.95
R2689213-2	5.95