



Stainless steel sling 4-leg RCMC-RCL-RCB

Product information



Rema®'s Grade 6 Stainless Steel Chain Slings are meticulously crafted using top-tier stainless steel (AISI 316), our slings are not just durable but also versatile. With the availability of individual components, we ensure a sustainable and customizable solution tailored to your specific lifting requirements. Our stainless steel assemblies are trusted across a myriad of industries such as construction, food & beverage, healthcare, aerospace, marine, and beyond.

Utilization Features:

1. **Durability:** Made with premium AISI 316 stainless steel, ensuring longevity and resistance to corrosion.
2. **Versatility:** Suitable for a range of lifting operations with various assembly options.
3. **Safety:** Comes with a CE-mark and a safety factor of 4, ensuring utmost safety during operations.
4. **Adaptability:** Individual component availability for a tailored lifting solution.

Markets/Applications:

- **Construction:** Ideal for heavy-duty lifting and construction site operations.
- **Food & Beverage:** Stainless steel ensures hygiene and cleanliness, making it perfect for food-related lifting tasks.
- **Medical:** Suitable for lifting medical equipment and supplies.
- **Aerospace:** Can be used for lifting aerospace components.
- **Marine:** Resistant to corrosion, making it perfect for marine applications.

Link to components

- 4 x [RC stainless steel chain](#) | [masterlink RCMC](#) | 4 x [connecting link RCL](#) | 4 x [clevis sling hook RCB](#) | [AISI 316 TAG](#)

Marking: CE-marked

Safety factor: 4

Grade: 6

Part Code	WLL ton
R2689406-1	1.89
R2689406-1.5	1.89
R2689406-2	1.89
R2689407-1	2.625
R2689407-1.5	2.625
R2689407-2	2.625
R2689408-1	3.36
R2689408-1.5	3.36
R2689408-2	3.36
R2689410-1	5.25
R2689410-1.5	5.25
R2689410-2	5.25
R2689413-1	8.925
R2689413-1.5	8.925
R2689413-2	8.925