


Ropetex 55

Product information



ROPETEX



Excellent Resistance to Rotation giving over three times more lifting height than a conventional 18 x 7 class rope. Flexibility is optimised by the unique strand and rope construction. Langs Lay construction combines excellent wear characteristics with efficient spooling on the drum.

RopeTex Ropes are lubricated with the very latest High Performance Wire rope lubricants to give excellent corrosion protection, fatigue life combined with low fling off

ISO 4309 Rope Category No: All Diameters **RCN.23-1**

Features: Very High Breaking Load

Material: High Carbon Steel

Marking: According to standard

Finish: Galvanised as standard

Standard: EN 12385-4

Fill factor: 0,64

RCN: 23-1

Part Code	Rope Diameter,	Tensile strength N/mm ²	Finish	Rope lay.	Min. Breaking force, kN	Steel area mm ²	Lubrication	Weight kg/100m	Delivery time
102100806300069	8	2,160	Galvanized	zZ	50.5	-	SupplierStandard	27.6	30
102100806270069	8	1,960	Galvanized	zZ	-	-	SupplierStandard	27.6	30
102100906300069	9	2,160	Galvanized	zZ	64	-	SupplierStandard	34.4	30

102100906270069	9	1,960	Galvanized	zZ	-	-	SupplierStandard	34.4	30
102101006300069	10	2,160	Galvanized	zZ	79	-	SupplierStandard	43	30
102101006270069	10	1,960	Galvanized	zZ	-	-	SupplierStandard	43	30
102101106300069	11	2,160	Galvanized	zZ	95.6	-	SupplierStandard	52	30
102101106270069	11	1,960	Galvanized	zZ	-	-	SupplierStandard	52	30
102101206300069	12	2,160	Galvanized	zZ	114	-	SupplierStandard	62	30
102101206270069	12	1,960	Galvanized	zZ	-	-	SupplierStandard	62	30
102101306300069	13	2,160	Galvanized	zZ	134	-	SupplierStandard	72	30
102101306270069	13	1,960	Galvanized	zZ	-	-	SupplierStandard	72	30
102101406300069	14	2,160	Galvanized	zZ	155	-	SupplierStandard	84	30
102101406270069	14	1,960	Galvanized	zZ	-	-	SupplierStandard	84	30
102101506300069	15	2,160	Galvanized	zZ	178	-	SupplierStandard	96	30
102101506270069	15	1,960	Galvanized	zZ	-	-	SupplierStandard	96	30
102101606300069	16	2,160	Galvanized	zZ	202	-	SupplierStandard	110	30
102101606270069	16	1,960	Galvanized	zZ	-	-	SupplierStandard	110	30
102101706300069	17	2,160	Galvanized	zZ	228	-	SupplierStandard	120	30
102101706270069	17	1,960	Galvanized	zZ	-	-	SupplierStandard	120	30
102101806300069	18	2,160	Galvanized	zZ	256	-	SupplierStandard	135	30
102101806270069	18	1,960	Galvanized	zZ	-	-	SupplierStandard	135	30
102101906300069	19	2,160	Galvanized	zZ	285	-	SupplierStandard	150	30
102101906270069	19	1,960	Galvanized	zZ	-	-	SupplierStandard	150	30
102102006300069	20	2,160	Galvanized	zZ	316	-	SupplierStandard	166	30
102102006270069	20	1,960	Galvanized	zZ	-	-	SupplierStandard	166	30

102102206300069	22	2,160	Galvanized	zZ	382	-	SupplierStandard	201	30
102102206270069	22	1,960	Galvanized	zZ	-	-	SupplierStandard	201	30
102102406300069	24	2,160	Galvanized	zZ	455	-	SupplierStandard	245	30
102102406270069	24	1,960	Galvanized	zZ	-	-	SupplierStandard	245	30
102102606300069	26	2,160	Galvanized	zZ	527	-	SupplierStandard	297	30
102102606270069	26	1,960	Galvanized	zZ	-	-	SupplierStandard	297	30
102102806300069	28	2,160	Galvanized	zZ	612	-	SupplierStandard	345	30
102102806270069	28	1,960	Galvanized	zZ	-	-	SupplierStandard	345	30