



Standard Reeve Crane Blocks 2 Sheaves

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

Part Code	WLL ton	Model	For wire Ø mm	Hooksize	Weight kg	Delivery time
6097SRB28516216E	16	SRB 285 .16 .2 .16 .E	16	6	95	30
6097SRB26014216E	16	SRB 260 .14 .2 .16 .E	14	6	130	30
6097SRB26016216E	16	SRB 260 .16 .2 .16 .E	16	6	130	30
6097SRB28516220EA	20	SRB 285 .16 .2 .20 .E .A	16	8	130	30
6097SRB28516220EB	20	SRB 285 .16 .2 .20 .E .B	16	8	150	30
6097SRB32016220E	20	SRB 320 .16 .2 .20 .E	16	8	160	30
6097SRB32016225E	25	SRB 320 .16 .2 .25 .E	16	8	205	30
6097SRB35519229E	29	SRB 355 .19 .2 .29 .E	19	8	250	30
6097SRB40022229E	29	SRB 400 .22 .2 .29 .E	22	8	320	30
6097SRB45024240E	40	SRB 450 .24 .2 .40 .E	24	12	550	30
6097SRB45026250E	50	SRB 450 .26 .2 .50 .E	26	16	550	30
6097SRB52826263E	63	SRB 528 .26 .2 .63 .E	26	16	980	30
6097SRB52828280E	80	SRB 528 .28 .2 .80 .E	28	20	1,000	30
6097SRB670282100E	100	SRB 670 .28 .2 .100 .E	28	20	2,240	30
6097SRB670322100E	100	SRB 670 .32 .2 .100 .E	32	20	2,240	30

Blueprint

