



Standard Reeve Crane Blocks 3 Sheaves

Product information

General:

- Standard Reeve Crane Blocks may be used on a wide variety of land based cranes such as mobile and crawler cranes. They are an excellent choice where frequent easy block change is not a required main feature, or lifting height is limited.
- Double sealed maintenance free roller bearings.
- Design Factor of Safety of 4:1.
- Forged high tensile steel DIN hooks.
- Ductile iron sheaves, featuring graphite lubricated groove.
- High impact resistant side plates.
- Operational temperature range -40 up to +80°C.
- Lubrication on hook suspension.
- Short design for increased lifting height.
- Safety latch with locking pin.
- C3M finish in signal yellow.

Options:

- Double hook.
- Double hook with shackle hole.
- Quad hook.
- Shackle stud eye.

Important:

Inquiries for custom versions are welcome!

Part Code	WLL ton	Model	For wire Ø mm	Hooksize	Weight kg	Delivery time
6097SRB26014325E	25	SRB 260 .14 .3 .25 .E	14	8	210	30
6097SRB26016325E	25	SRB 260 .16 .3 .25 .E	16	8	210	30
6097SRB28516329E	29	SRB 285 .16 .3 .29 .E	16	8	210	30
6097SRB32016329E	29	SRB 320 .16 .3 .29 .E	16	8	225	30
6097SRB35519332E	32	SRB 355 .19 .3 .32 .E	19	10	325	30
6097SRB36019340E	40	SRB 360 .19 .3 .40 .E	19	12	455	30
6097SRB40022340E	40	SRB 400 .22 .3 .40 .E	22	12	500	30
6097SRB40022350E	50	SRB 400 .22 .3 .50 .E	22	16	500	30
6097SRB40022350E	50	SRB 400 .22 .3 .50 .E	22	16	540	30
6097SRB45022363E	63	SRB 450 .22 .3 .63 .E	22	16	680	30
6097SRB45024363E	63	SRB 450 .24 .3 .63 .E	24	16	770	30
6097SRB45026363E	63	SRB 450 .26 .3 .63 .E	26	16	770	30
6097SRB52826380E	80	SRB 528 .26 .3 .80 .E	24	20	1,270	30
6097SRB52826380E	80	SRB 528 .26 .3 .80 .E	26	20	1,270	30
6097SRB528263100E	100	SRB 528 .26 .3 .100 .E	26	25	1,270	30
6097SRB528283100E	100	SRB 528 .28 .3 .100 .E	28	25	1,270	30
6097SRB670283125E	125	SRB 670 .28 .3 .125 .E	28	25	2,900	30
6097SRB670323125E	125	SRB 670 .32 .3 .125 .E	32	25	2,900	30

Blueprint

